



Rigel Gear Oils

Dyna-Plex 21C® Rigel Gear Oils are the economical choice for a variety of heavy duty applications, including over-the-road trucks and off-highway equipment. These oils provide extreme load carry capacity for bevel and spiral bevel gears.

Dyna-Plex 21C Rigel Gear Oils are fortified with anti-oxidants and corrosion inhibitors to resist damage from rust and oxidation.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 90</u>	<u>SAE 85W-140</u>
Viscosity @ 40°C, cSt	D-445	223.10	348.80
Viscosity @ 100°C, cSt	D-445	18.80	24.86
Viscosity Index	D-2270	95	96
Flash Point, COC, °C (°F)	D-92	180 (356)	185 (365)
Pour Point, °C (°F)	D-97	-12 (10)	-17 (0)
Color	D-1500	4.5	5.0
Gravity, °API	D-287	26.5	25.6
Copper Strip Corrosion (250°F)	D-130		1a
Foam Test	D-892		0 ml, 3 seq.
Timken OK Load	D-2509		50

Meets or exceeds the following tests and requirements:

- API Service Classification – GL-5, MT-1
- Military Specification – MIL-PRF-2105E
- International Harvester – B-22
- Mack – GO-J