



Slideway Lube

Dyna-Plex 21C® Slideway Lubes are specifically designed for the lubrication of machine tool slides and tables. They are formulated with high quality mineral oils and additives for tackiness and wear, oxidation, and corrosion resistance, and required stick-slip properties.

Dyna-Plex 21C Slideway Lubes possess outstanding cutting fluid compatibility. They exhibit excellent frictional characteristics. The multi-functional performance of the Dyna-Plex 21C Slideway Lubes allows them to be used in hydraulics and industrial gear applications, giving the benefit of reduced lubricant inventories.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>ISO 68</u>	<u>ISO 220</u>
Viscosity @ 40°C, cSt	D-445	68.0	220.0
Viscosity @ 100°C, cSt	D-445	8.80	19.4
Viscosity Index	D-2270	100	100
Flash Point, °C (°F)	D-92	200 (392)	210 (410)
Pour Point, °C	D-97	-24	-15
API Gravity	D-287	27.5	26.5

Dyna-Plex Slideway Lubes meet the following specification:
Wet/Dry Filterability for Hydraulic Performance
Brugger Performance
Cincinnati Milacron – P-47 (ISO 68), P-50 (ISO 220)