



Synzol Heavy Duty Automatic Transmission Fluid

Dyna-Plex 21C® Synzol Heavy Duty (HD) Automatic Transmission Fluid (ATF) is a premium quality, synthetic lubricant used in heavy duty automatic transmissions. It is formulated with the quality level to support extended drain intervals, where applicable.

Dyna-Plex 21C Synzol HD ATF provides excellent thermal and oxidative stability for long transmission life and exceptional all weather performance in both hot and cold temperature extremes. It is shear stable for long term viscosity protection and contains durable friction properties to ensure smoother shifting transmissions.

This product is designed for use in heavy duty automatic transmissions typically found in bus fleets and over-the-road trucks.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>TEST SPECIFICATIONS</u>
Viscosity @ 40°C, cSt	D-445	37.14
Viscosity @ 100°C, cSt	D-445	7.41
Brookfield Viscosity @ -40°C, cP		8411
Density @ 60°F (lb/gal)		7.038
Flash Point, COC, °C (°F)	D-92	230 (446)
Pour Point, °C (°F)	D-97	-55 (-67)
Copper Strip Corrosion, 150°C, 3 hr.	D-130	1b
Four-Ball Wear Test 40 kg, 75°C, 1200 rpm, 1 hr, mm.	D-4172B	0.45

Meets or exceeds the following tests and requirements:

- ZF TE-ML 14C
- Voith G 607, G 1363

Suitable for use in applicable:

- Pre-2006 GM automatic transmissions
- Pre-2007 Ford automatic transmissions
- Allison automatic transmissions