

## **Synzol Transmission Oil**

Dyna-Plex 21C<sup>®</sup> Synzol Synthetic Manual Transmission Fluid is recommended for applications where heat and wear present major problems. These applications include manual transmissions where GL-1, GL-2, GL-3, and GL-4 type fluids are required.

Dyna-Plex 21C Synzol is a full synthetic transmission fluid designed for today's transmission synchronizers and is formulated for years of trouble-free shifting.

Dyna-Plex 21C Synzol meets Eaton and Meritor 750,000 mile extended warranty requirements, allowing the user to go 500,000 miles between drains in Eaton, Meritor and Mack transmissions.

<u>PROPERTY</u>	ASTM TEST METHOD	SAE <u>50</u>
Viscosity @ -18°C, cP	D-2602	N/A
Viscosity @ 40°C, cSt	D-445	160
Viscosity @ 100°C, cSt	D-445	18.60
Viscosity Index	D-2270	133
Flash Point, COC, °C (°F) Pour Point, °C (°F)	D-92 D-97	249 (480) -40 (-40)
Color	D-1500	Red
Gravity, °API	D-287	23.0
Four-Ball Wear – scar dia, mm. Copper Corrosion	D-4172B D-130	0.38 1b

Meets or exceeds the following specifications: API GL-1, GL-2, GL-3, GL-4, MT-1 Eaton Corporation – PS164 and PS081 Mack – TO-A Plus Meritor 0-81 International TMS-6816 Volvo STD 97305