



SYNZOL EXTREME HD ATF

Dyna-Plex 21C® Synzol Extreme Heavy Duty Automatic Transmission Fluid (ATF) is a premium quality, synthetic lubricant used in heavy duty automatic transmissions. It is formulated with the quality level to support extended drain intervals, where applicable.

Dyna-Plex 21C Synzol Extreme Heavy Duty Automatic Transmission Fluid provides excellent thermal and oxidative stability for long transmission life and exceptional all-weather performance in both hot and cold temperature extremes. It is shear stable for long term viscosity protection and contains durable friction properties to ensure smoother shifting transmissions.

This product is designed for use in heavy duty automatic transmissions typically found in bus fleets and over-the-road trucks.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>TEST SPECIFICATIONS</u>
Viscosity @ 40°C, cSt	D-445	34.50
Viscosity @ 100°C, cSt	D-445	7.00
Viscosity Index	D-2270	170
Brookfield Viscosity @ -40°C, cP		11,000
API Gravity @ 60°F		35.5
Density @ 60°F (lb/gal)		7.055
Color		Red
Flash Point, COC, °C (°F)	D-92	230 (446)
Pour Point, °C (°F)	D-97	-55 (-67)
Copper Strip Corrosion, 150°C, 3 hr.	D-130	1b
KRL Shear 100hr, mm ² /s	CEC-L-45-A-99	6.0

This product has the following approvals:

Allison Transmission TES 668® (Approval Number: 668-10482024)
Backwards compatible with TES 295®, TES 389® and TES 468®.



Meets or exceeds the following tests and requirements

Ford XT-2-QDX, XT-5-QM
GM D-IIIH, D-IIIG, D-IIID
Daimler DTFR 13C190 (Formerly MB 236.92)
JASO M315 Type 1A
MAN 339 Type IV
Voith H55.6335, H55.6336
Volvo 97340, 97341

SYNZOL EXTREME HD ATF/07.10.24



PROVEN PROTECTION