

## **EMB Grease**

Dyna-Plex 21C® EMB Grease is a semi-synthetic ISO 150 polyurea grease specifically designed for use in rolling element anti-friction bearings operating under extreme temperatures. The organic polyurea thickener system contains no metal ions which act as catalysts for oxidation. Dyna-Plex 21C EMB Grease was designed with special antioxidants and corrosion inhibitors to ensure long life of rolling bearings operating under severe temperature and high humidity. The extended service temperature range of -22°F to 320°F and high-speed factor of 500,000 nDm makes EMB Grease the ideal lubricating grease for electric motor bearings designed to be lubricated for life.

NLGI

PROPERTY <u>2</u>

Color Beige

Texture Homogenous

Base Oil Synthetic hydrocarbon/mineral oil

**Base Oil Properties** 

Viscosity @ 40°C, cSt 160
Viscosity @ 100°C, cSt 18
Viscosity Index 125
Thickener Type Polyurea
Density @ 20°C 0.9
Service Temperature °F -22 to 320

 Service Temperature, °F
 -22 to 320

 Drop Point, °C (°F)
 > 250 (482)

 Penetration-Worked 60 ds
 265-295

Oil Separation <5

4-Ball Wear 0.5 mm, 0.54 mm

Weld Load 160 kg Corrosion Preventative Properties Pass

**Corrosion Preventative Properties** 

EMCOR 1 Copper Corrosion 1a

## Shelf Life:

Product shelf life is 2 years from the data of manufacture, after which the product should be recertified prior to use.